



| Technical Data | U.S. Units | Metric Units |
|--------------------------------|-------------------------------|--------------|
| Cavity | | T-11A |
| Body Features | | (See Notes) |
| Body Type | | Line mount |
| Interface | | None |
| Open Cavity Quantity | | 1 |
| Weight | 2.016 lb. | 0,915 kg. |
| Mounting Hole Diameter | .34 in. | 8.6 mm |
| Mounting Hole Depth | | Through |
| Mounting Hole Quantity | | 2 |
| Includes integral cartridge(s) | Yes (see Included Components) | |

Notes

- Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
- This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.
- Body Features: Ninety degree with reverse flow check, accepts standard and weatherized coils.

| Port Headings | | |
|---------------|-------------|-----------|
| Product | Port | Size |
| A2J | Ports 1 & 2 | SAE 8 |
| A2J | Port 3 | SAE 6 |
| A2J | Gage Port | 1/4" NPTF |

| | | | | | | |
|-------------|-------------|---|-------------|--|--------------------------|-------|
| 2 | CXDA-XCN | | CHECK VALVE | 1 | | |
| 1 | 174-485-005 | 6061-T6 ALUMINUM | BODY | 1 | | |
| ITEM | PART NO. | SETTING | MATERIAL | PART NAME | QTY | |
| | MODEL | | A2J | ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE | FIRST ANGLE THIRDA ANGLE | |
| DESCRIPTION | | T-11A Line mount (See Notes for Body Features) | DATE | SCALE | DWG SIZE | SHEET |
| | | Oct-04-23 | 1.182 | C | 1 | |

