




Technical Data	U.S. Units	Metric Units			
Cavity	T - I 7 A				
Body Features	Ninety degree with rever	rse flow check - sequence			
Body Type	Line mount				
Interface	None				
Open Cavity Quantity					
Weight	5.863 lb.	2,659 kg.			
Mounting Hole Diameter	.41 in.	10,4 mm			
Mounting Hole Depth	Through				
Mounting Hole Quantity	2				
Includes integral cartridge(s)	Yes (see Included Components)				








<u>Notes</u>

- 1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

 2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings						
Product	Port	Size				
H6F	Ports I & 2	I I/4" NPTF				
H6F	Port 3	I/4" NPTF				
H6F	Gage Port	I/4" NPTF				



2	CXHAXCN				CHEC	CHECK VALVE		
I	150-755-003		6061-T6 ALUMINUM		BODY			1
T E M	PART NO.	SETTING	MATER	IAL		PART NAME		
MODEL	H 6 F		ALL DIMENSIONS IN I VIEWS ARE THIRD AN				FIRST ANGLE THIRD	ANGLE
T-17A Line mount (See Technical Data for Body Features)		N o v - 0 - 2 4	0 . 799	DWG SIZE	SHEET	SUD hydrauli	®	